



LAMPADE SPOT LED

LEXAR 60

GU5.3



CRI>80



25.000h



≥15.000 Switch



Saving



Energy Class



Not Dimmable



Multiled

PRO LINE

Codice Prodotto	Attacco	Watt	Comparazione Halogen	Lumen	Colore Luce (K)	Volt Hertz	Apertura Fascio	Milliamp.	Fattore Potenza	Imballo Pz
product code	base type	power	rendering watt	lm	colour temp.	voltage hertz	beam	current mA	power factor	Inner/Master
LX60-065330	GU5.3	6W	40W	385Lm	3000K	12VDC/AC	60°	640mA	≥0,50	10/50 pz
LX60-065360	GU5.3	6W	40W	405Lm	6000K	12VDC/AC	60°	640mA	≥0,50	10/50 pz
LX60-085330	GU5.3	8W	50W	470Lm	3000K	12VDC/AC	60°	850mA	≥0,50	10/50 pz
LX60-085360	GU5.3	8W	50W	500Lm	6000K	12VDC/AC	60°	850mA	≥0,50	10/50 pz

- Alimentazione con trasformatori elettromagnetici e non elettronici
Power with electromagnetic transformers, no electronic

Articolo	D1 Diametro Ø	L1 Altezza	Peso
item	diameter	height	weight
LX60 6W GU5.3	50 mm	45 mm	38 gr
LX60 8W GU5.3	50 mm	48 mm	53 gr

