



LAMPADINE SPECIALI LED

PIXY G4 12Volt

rivestimento silconico


rivestimento silconico



PIXYFULL 1.5W



PIXYFULL 3W



PIXYPLT



CRI>82 (PIXYFULL 1.5W)
CRI>80 (PIXYFULL 3W - PIXYPLT)



25.000h (PIXYFULL 1.5W)
15.000h (PIXYFULL 3W) - 30.000h (PIXYPLT)



≥15.000 Switch (PIXYFULL 1.5W - PIXYPLT)
≥10.000 Switch (PIXYFULL 3W)



Saving



Energy Class (PIXYFULL 1.5W)



Energy Class (PIXYFULL 3W)
(PIXYPLT)

Codice Prodotto	Attacco	Watt	Comparazione Tradizionale	Lumen	Colore Luce (K)	Volt Hertz	Apertura Fascio	Milliamp.	Fattore Potenza	Imballo Pz
product code	base type	power	rendering watt	lm	colour temp.	voltage hertz	beam	current mA	power factor	Inner/Master
PIXYFULL-150430	G4	1.5W	15W	110Lm	3000K	12VDC/AC	360°	150mA	≥0.50	12/96 pz
PIXYFULL-030430	G4	3W	30W	200Lm	3000K	12VDC/AC	360°	200mA	≥0.40	12/96 pz
PIXYPLT-020430	G4	2W	20W	170Lm	3000K	10-30VDC/10-20VAC	180°	210mA	≥0.50	12/96 pz

• Alimentazione con trasformatori elettromagnetici e non elettronici
Power with electromagnetic transformers, no electronic



Not Dimmable

Articolo	D1	L1	Peso
item	Diametro Ø	Altezza	weight
PIXYFULL 1.5W G4	10 mm	33 mm	8 gr
PIXYFULL 3W G4	16 mm	38 mm	8 gr
PIXYPLT 2W G4	30 mm	39 mm	4 gr

