


Local Code:


## **CUSTOMER DATASHEET**


Printed: 17/09/2019

**Product Management** Transportation Europe

D31080C12-A Created: 11/11/2013 Central Article Code: Modified: TA955 30/01/2015







**Final Outlook** D3112-A Approval date 15/12/2013

I LIN ONMANOLO			
Voltage (V):	12 V		
C20 (Ah):	95.0	20 h	
Cranking (A):	800	EN	
Charge:	WET		
Technology:	Vented/Flooded		
Grid:	Ca/Ca		

**PERFORMANCES** 

D31 **GREY DARK** Type: Korean B1 Hold Down:

H.D. Adapter: No

Type:

COVER Double with Inte GREY DARK

CONTAINER

Polarity: ETN 1

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central Filter: 2 Filters Lateral Plug: No

## **STD. DIMENSIONS**

Length (mm ± 2): 306 Width  $(mm \pm 2)$ : 173 Height (mm ± 2): 222 Total Weight (kg ± 5%): 23.60

**PLUGS** 

**GREY DARK** Type: 1 x Vent Seale

**HANDLES** 

1 x Integrated **GREY DARK** Type:

**OTHERS** 

**Degassing Tube:** No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.