


CUSTOMER DATASHEET


Printed: 25/02/2019


Product Management
Transportation Europe

Central Article Code: D06120C01-A Created: 21/05/2014

Local Code: TB802 Modified: 20/12/2018







Final Outlook D0601-A Approval date 01/10/2005

| | _ | | | |
|---|-----------|-------|-----|------|
| _ | | | | ICES |
| - | . – . | IK IV | ΙДΝ | – 5 |
| _ | | | | |

Voltage (V): 12 V

C20 (Ah): 215.0 20 h Cranking (A): 1200 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

CONTAINER

Type: D06 BLACK Hold Down: B0

H.D. Adapter: No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 518

 Width (mm \pm 2):
 279

 Height (mm \pm 2):
 240

 Total Weight (kg \pm 5%):
 54.90

PLUGS

Type: 6 x M27 BLACK

HANDLES

Type: 2 x Rope (Rigid holde BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.