



avvolgitubo statico con tubo alta flessibilità 6 m
static hose reel with super flexible hose 6 m



serbatoio detergente alta pressione
high pressure detergent tank



battistrada in gomma
rubber wheels



interruttore rotativo a 3 posizioni off/Eco Speed/Full Speed
3 positions rotative switch off/Eco Speed/Full Speed



filtro ingresso acqua ispezionabile
inspectable water intake filter



Caratteristiche Generali

- Manico con avvolgitubo statico per tubo AP (6 m)
- Pompa a 3 pistoni assiali comandati dal piattello oscillante, testa in alluminio
- Pistoni in acciaio inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Motore universale a due velocità con protezione termica
- Lunghezza cavo elettrico 5 m

General Features

- Two-wheel trolley with handle and static hose reel (6 m HP hose)
- 3 Axial stainless steel pistons wobble-plate pumps
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Dual speed single-phase universal motor with thermal protector
- Electric cable length 5 m



MOD	COD	MAX	MAX					NET		
		bar	psi	l/h	gph	kW	rpm	Hz	V	kg
2.0 PE	14986	160	2300	460	122	2,2	2800	50-60	220-240~	10,3

Accessori standard Standard accessories



46328 46332 (42 cm) 46541 (6 m)



46572 3085530 41565 46327

