



PLUS 160 - 210

inverter

WIDE INPUT VOLTAGE
170-250

CONNECTABLE TO POWER GENERATOR

100% DUTY CYCLE

DINSE 35-50

CE

SAFETY LVD IEC 60974-1

EMC IEC 60974-10

IGBT INSULATED GATE BIPOLAR TRANSISTOR

21S IP

H CLASS



Optional

WELDING HELMET DIN 4/9-13



HELMET 1500-G
COD. 90356

WELDING HELMET DIN 11 FIX



HELMET 2000 E 11
COD. 90385

GLOVES



COD. 90330

APRON



COD. 90316

MAGNETIC HELP



COD. 88031

HAMMER



COD. 80010

ELECTRODES E6013 RUTILE



Ø2,0mm 25pcs
50pcs
Cod. 90470
Cod. 90480
Ø2,5mm 25pcs
50pcs
Cod. 90471
Cod. 90481
Ø3,2mm 15pcs
Cod. 90490

ELECTRODES E6013 RUTILE



Ø2,0mm 402pcs
Cod. 90731
Ø2,5mm 303pcs
Cod. 90745
Ø3,2mm 202pcs
Cod. 90755



Accessories Included



Elettrodi/Electrodes

Rutilici/Rutile - AWS E6013
Inox/Stainless Steels - AWS E308
Basici/Basic - AWS E7018
Ghisa/Cast Iron - AWS A5.15

Technical specifications

	CODE	V	P	Vo	I ₂ [A]	K _v /I ₁ [A]	X ₂₀ °C	Electrodes (mm)	Box volume	Kg	Box size (mm)	PCS per masterbox	PCS per Euro pallet	BAR CODE
	Order code	Input voltage	Absorbed power	No load voltage	Welding current	Duty cycle	Duty cycle	Electrodes (mm)	Box volume	Box weight	Box size (mm)	PCS per masterbox	PCS per Euro pallet	Bar code
			KVA KW											
PLUS 160	55716	230V~1ph	6,5 5,0	65	10-160	40/160	160A@100%	1,6-4	0,035m ³	8,7	460x230x341	1	35	8004386557167
PLUS 210	55721	230V~1ph	8,5 6,5	65	15-200	40/200	200A@100%	1,6-5	0,035m ³	9,1	460x230x341	1	35	8004386557211