



Caratteristiche Generali

- Pompa a 3 pistoni assiali comandati da piattello oscillante (2591, 3590) o con sistema biella-manovella (4590)
- Pistoni in acciaio inox temprato
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Motore elettrico a induzione con protezione termica
- Pressostato di sicurezza per spegnimento della caldaia in caso di mancanza acqua
- Caldaia verticale, doppia serpentina e fondo in materiale refrattario
- Serbatoio gasolio 4 l
- Filtro acqua e filtro aspirazione gasolio
- Tubo rinforzato con treccia in acciaio (8 m)

General Features

- 3 Axial stainless steel pistons wobble-plate pump (2591, 3590) or with connecting rod system (4590)
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Single-phase induction electric motor with thermal protector
- With safety pressure switch to shut down the boiler in case of lack of water
- Vertical boiler with double heating coil and refractory compound base
- Fuel tank capacity 4 l
- Water filter and fuel inlet filter
- Steel braided reinforced hose (8 m)



MOD	COD	MAX	MAX		NET						
		bar max	psi max	l/h max	gph max	kW	rpm	Hz	V	kg	°C Max
4590	24426-V	160	2320	500	132	2,5	2800	50	230~	52,8	90

Accessori standard Standard accessories

