тоуотомі

Desiccant Type Dehumidifier TD-ZB80



Non		CE	CFK	years
-----	--	----	-----	-------

NEW 'ECH<u>NOLOGY</u>

efficient at low

temperature

EAN code	4963505828493		
Colour	White		
Capacity	8 L/day		
Power consumption (min./max)	250 W / 620 W		
Tank capacity	4.0 L		
Suitable space	15 - 25 m² / 37 - 75 m³		
Operation Temperature	1 - 40 °C		
Dimension unit / carton	350 x 240 x 506 mm (W x D x H) / 398 x 282 x 570 mm (W x D x H)		
Weight (net. / gross)	7.2 Kg / 8.3 Kg		

Desiccant type dehumidifier



This model features a desiccant wheel instead of a rotary compressor, it will keep on dehumidifying at maximum capacity even below an ambient temperature of 15°C. Ideal for cellars, garages, caravans, boats, storage rooms. No compressor, no harmful refrigerant gas

but low noise during operation.

Dew condensation preventing mechanism

Humidity sensor controls room humidity from 45% to 50% automatically to prevent dew condensation on the wall and window.

Automatic operation

This unit is equipped with humidity sensor and room humidity is controlled automatically at 45% - 50%.

Laundry mode

Laundry mode can make dry rapidly the hanged laundry in the room. you can select turbo mode or saving mode depending your laundry amount.

Auto swing air louvre outlet

The unit has a top air louver outlet, with a wide 180 degrees angle, which makes it easy to dry your laundry or have it even blown downward for floor drying. the louver has a 3 automatic swing setting, wide – up or front.

Unique design, compact body & lightweight

Model TD-ZB80 has a unique compact design and is also lightweight and easy to carry (7.2 kg). a new feature are the two lateral air intakes, which enables the unit to put it close against the wall, very convenient for smaller rooms.

Auto - restart function

In case of a power failure the unit will stop of course, but when power is on again, the unit will start automatically regaining its former settings.

Big size water tank (4.0 liter)

The big (lateral) water tank of 4.0 liters will minimize the numbers of drainages per day (max. 2 times / 24 hrs), it can easily be taken out from the side, once the unit is put straight against the wall. The water tank has a built in handle and a cover to prevent the watertank to spill water during handling. In case of a more permanent setting, you can easily connect a permanent drain tube into the unit straight to the sink. Especially when the unit will be installed at a higher level against the wall this permanent drain will be highly effective.

Anti bacterial / allergic air filter

The new white clean design unit with delicate silver plating is also equipped with an easy access operation panel (different automatic preset programs), a built in handle for easy carrying and anti bacterial filter which can easily be cleaned and in time even be replaced.

Off-timer

The unit has an off-timer function which can be selected from 2 hrs. to 4 hrs. or 8 hrs.

Toyotomi Europe Sales B.V. Huygensweg 10, 5466 AN Veghel The Netherlands Tel: +31 (0)413 82 02 95 www.toyotomi.eu • info@toyotomi.eu

