

DXPW005E



400V-50HZ



810L/H



200BAR



60°C



5,0kW



HRC.0 TRIPLEX PUMP

High quality 1450 rpm motor pump powered by a **3 PHASE** electric motor with **THERMAL PROTECTION**.

Brass pump head.

CRANKSHAFT system with **THREE CERAMIC COATED PISTONS** to give longer useable life.

Double **TEXTILE RUBBER GASKETS** for improved protection.

Motopompa di alta qualità a 1450 rpm alimentata da motore elettrico trifase a induzione con protezione termica.

Testa pompa in ottone.

Sistema biella-manovella con 3 pistoni assiali rivestiti in ceramica.

Doppia guarnizione in gomma-tela per una lunga durata.



TECHNICAL DATA

Model/Modello	DXPW005E
AR code	25157
EAN code	8016287251570
Max. Pressure (bar)	200
Max. Flow Rate l/h (High Pressure)	810
Absorbed power (W - Kw)	5000 - 5,0
Type motor (Phase)	3~
RPM (pump)	1450
Voltages (V) - Frequency (Hz)	400 - 50
Max Water Temperature (C°)	60
Net Weight (Kg)	46,0
Pump material	Brass
Pistoni / Pistons	Acciaio-ceramica / Steel-ceramics
Sistema / System	Manovella / Crank Shaft
Total Stop System	•
Self priming	•



Built-in unloader valve with **TSS**.

Valvola di regolazione integrata con TSS.



Glycerin filled **precision** pressure gauge.

Manometro di precisione a bagno di glicerina.



Pump oil tank with **CLEAR SIGHT GLASS** for oil level control.

Serbatoio dell'olio con dispositivo visore del livello.



ACCESSORIES

Cod. 43516
HP reinforced hose 10m
Tubo armato AP 10m

Cod. 43504
Trigger gun 3/8" Pistola 3/8"
M22x1,5(M)/M22x1,5(F)



Cod. 43510
HI/LOW pressure lance
Lancia ALTA/BASSA pressione