

DXPW002CE



230V-50HZ



510L/H



180BAR



60°C



2,9kW



HJR.0 TRIPLEX PUMP

High quality 2800 rpm motor pump powered by a **SINGLE-PHASE** electric motor with **THERMAL PROTECTION**.

Brass pump head.

CRANKSHAFT system with **THREE CERAMIC COATED PISTONS** to give extended useable life.

Double **HNBR RUBBER GASKETS** for improved protection.

Motopompa di alta qualità a 2800 rpm alimentata da motore elettrico monofase a induzione con protezione termica.

Testa pompa in ottone.

Sistema biella-manovella con 3 pistoni assiali rivestiti in ceramica.

Doppia guarnizione in gomma HNBR per una lunga durata.





Built-in unloader valve with **TSS**.

Valvola di regolazione integrata con TSS.



Glycerin filled **precision** pressure gauge.

Manometro di precisione a bagno di glicerina.



Pump oil tank with **OIL DIPSTICK** for easier control.

Serbatoio dell'olio con dispositivo visore del livello.



TECHNICAL DATA

Model/Modello	DXPW002CE
AR code	26773
EAN code	8016287267731
Max. Pressure (bar)	180
Max. Flow Rate l/h (High Pressure)	510
Absorbed power (W - Kw)	2900 - 2,9
Type motor (Phase)	1~
RPM (pump)	2800
Voltages (V) - Frequence (Hz)	230 - 50
Max Water Temperature (C°)	60
Net Weight (Kg)	19.5kg
Pump material	Brass
Total Stop System	•
Self priming	•

ACCESSORIES

Cod. 43515
HP reinforced hose 8m
Tubo armato AP 8m



Cod. 43504
Trigger gun 3/8" Pistola 3/8"
M22x1,5(M)/M22x1,5(F)



Cod. 46063
Lance with HI/LOW pressure head
Lancia ALTA/BASSA pressione

