



3 Series 399

IDROPULTRICI ALTA PRESSIONE
high pressure washers



porta accessori
built-in accessories
holder

battistrada in
gomma
rubber wheels

avvolgitubo statico
static hose reel

serbatoio detergente
integrato
built-in detergent
tank

filtro ingresso acqua
ispezionabile
inspectable water intake filter

Caratteristiche Generali

- Carrello a due ruote completo di manico ed avvolgitubo (Tubo AP 6 m)
- Pompa a 3 pistoni assiali comandati dal piattello oscillante
- Pistoni in acciaio inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Motore elettrico monofase a induzione con protezione termica
- Aspirazione detergente diretta con serbatoio incorporato
- Capacità del serbatoio detergente 1,4 l
- Lunghezza cavo elettrico 5 m

General Features

- Two-wheel trolley with handle and hose reel (6 m HP hose)
- 3 Axial stainless steel pistons wobble-plate pump
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Single-phase induction motor with thermal protector
- Built-in detergent tank for direct suction
- Detergent tank capacity 1.4 l
- Electric cable length 5 m



INDUCTION



WOBBLE
PLATE



ALUMINUM

TSS®
Total Stop
SYSTEM



MAX
50°C 122°F



IPX5-S1

MOD	COD	 MAX	 MAX						 KG NET	
		bar	psi	l/h	gph	kW	rpm	Hz	V	kg
399	14588	140	2000	450	119	2,0	2800	50	220-240~	21



Accessori standard Standard accessories



41561



41563
(42 cm)



41564



41562 (6 m)



41565



41583



3085530