

Dehumidifier TD-2412



Dehumidifier

EAN code	--	--	4963505063924
Power Supply	Rated Voltage	V-	220 - 240
	Rated Frequency	Hz	50Hz
	Phases	--	1
Rated Dehumidification Capacity	L/D		12
Power Input (35 °C,80%RH)	W		240
Air Flow Volume (H/M/L)	m3/h		H:110, L:70
Application Area	m3		50 - 75
Sound Pressure Level (H/M/L), 1.5Meter Distance	dB (A)		H:38, L:34
Set Humidity Range	%		30 - 90
Bucket Capacity (Water tank)	L		2.2
Control Type	--		Touch Control
Dimension (W×H×D)	mm		220 x 458 x 335
Dimension of Carton Box (W×H×D)	mm		417 x 255 x 498
Dimension of Package (W×H×D)	mm		417 x 255 x 498
Net Weight	kg		10.7
Gross Weight	kg		11.6
Refrigerant	--		R290
Refrigerant Charge	g		40
Loading quantity	Loading Quantity (20' Container)	unit	484
	Loading Quantity (40' Container)	unit	992
	Loading Quantity (40' HQ container)	unit	1265

Water Level Indicator/Location	✓
Removable Bucket/Location	✓
External Drain Connector	✓
Easy Roll Casters	YES mounted
Water Full Indicator	✓
Memory / Auto restart	✓
Auto Fan	✓
Light indication for humidity level	✓
WiFi Preinstalled	✓
Quiet Design	✓
I Feel *	✓
Timer	✓
Automatic Defrost	✓
Real-time display of ambient humidity	✓
Self Diagnosis	✓
Several Optional Healthy Filters (Active Carbon, Catechin, Anti-mildew, Electrostatic Dedust, Silver Ion Sterilizing Material, Cold Catalyst , Photocatalyst etc.)	Triple Action 3 in 1 filter
Hose for continuous drainage	✓
Ionizer	✓
Touch Panel	✓
LED	✓

* "I Feel" means Auto Smart. Automatically adjusts humidity according to changes in ambient temperature to provide users with a more comfortable environment.