

Dehumidifier TD-2420



Dehumidifier

EAN code	--	--	4963505830977
Power Supply	Rated Voltage	V-	220-240
	Rated Frequency	Hz	50
	Phases	--	1
Rated Dehumidification Capacity	L/D		20
Power Input (35 °C,80%RH)	W		325
Air Flow Volume (H/M/L)	m3/h		140
Application Area	m3		90 - 130
Sound Pressure Level (H/M/L), 1.5Meter Distance	dB (A)		<=47
Set Humidity Range	%		40 - 80
Bucket Capacity (Water tank)	L		3.5
Control Type	--		Electronic control
Dimension (W×H×D)	mm		344 x 561 x 250
Dimension of Carton Box (W×H×D)	mm		367 x 605 x 277
Dimension of Package (W×H×D)	mm		367 x 605 x 277
Net Weight	kg		13.7
Gross Weight	kg		15.3
Refrigerant	--		R290
Refrigerant Charge	g		90
Loading quantity	Loading Quantity (20' Container)	unit	393
	Loading Quantity (40' Container)	unit	804
	Loading Quantity (40' HQ container)	unit	1072

Water Level Indicator/Location	✓
Removable Bucket/Location	✓
External Drain Connector	✓
Easy Roll Casters	YES mounted
Water Full Indicator	✓
Memory / Auto restart	✓
Light indication for humidity level	✓
WiFi Preinstalled	✓
Quiet Design	✓
Timer	24H
Automatic Defrost	✓
Real-time display of ambient humidity	✓
Tank Filled Protection	✓
Self Diagnosis	✓
Several Optional Healthy Filters (Active Carbon, Catechin, Anti-mildew, Electrostatic Dedust, Silver Ion Sterilizing Material, Cold Catalyst , Photocatalyst etc.)	Active Carbon
Hose for continuous drainage	✓
Touch Panel	✓
LED	✓