

EVO 160

STANLEY
FATMAX

ELECTRODES

Rutile - AWS E6013
Stainless Steels - AWS E308
Basic - AWS E7018



10,5 KVA

TECHNICAL SPECIFICATIONS	EVO 160	
Main Voltage - Tension de réseau - Voltaje de red - Tensão de rede Tensione di rete - Netzwerkspeisung - Сетевое напряжение	230V, 50-60Hz	
Absorbed Power - Puissance absorbée - Potencia absorbida - Potência absorvida - Potenza assorbita - Absorbierte Kraft - поглощенная мощность (MAX)	6,8 kVA 5,2 kW	MMA
No load Voltage - Tension à vide - Tensión en vacío - Tensão de vácuo - Tensione a vuoto - Vakuumspannung - Вакуумное напряжение	82V	
Welding Current - Courant de soudage - Corriente de soldadura - Corrente de soldagem - Corrente di saldatura - Schweißstrom - Сварочный ток	15-160A	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho - Fattore di servizio - Einschaltdauer - Соотношение прерывистости - EN 60974-1	20/160A	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho - Fattore di servizio - Einschaltdauer - Соотношение прерывистости - 20° C	160A@60%	
Min-Max Electrode - Electrode Min-Max - Electrodo min-max - Electrodo min-max - Elettrodo Min-Max - Elektrode min-max - Электрод min-max	1,6-4,0 mm	
Absorbed Power - Puissance absorbée - Potencia absorbida - Potência absorvida - Potenza assorbita - Absorbierte Kraft - поглощенная мощность (MAX)	4,4 kVA 3,3 kW	TIG LIFT
No load Voltage - Tension à vide - Tensión en vacío - Tensão de vácuo - Tensione a vuoto - Vakuumspannung - Вакуумное напряжение	14V	
Welding Current - Courant de soudage - Corriente de soldadura - Corrente de soldagem - Corrente di saldatura - Schweißstrom - Сварочный ток	15-160A	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho - Fattore di servizio - Einschaltdauer - Соотношение прерывистости - EN 60974-1	20/160A	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho - Fattore di servizio - Einschaltdauer - Соотношение прерывистости - 20° C	160A@60%	
Min-Max Electrode - Electrode Min-Max - Electrodo min-max - Electrodo min-max - Elettrodo Min-Max - Elektrode min-max - Электрод min-max	1,6-2,4 mm (tungsten)	
Box volume - Volume de la boîte - Volumen caja de carton - Volume caixa de cartão - Volume scatola - Kartonschachtel Volumen - Объем коробки	0,026m³	
Box Size - Taille de la boîte - Dimensiones caja de carton - Dimensões caixa de cartão - Dimensione scatola - Kartonschachtelgröße - Размер коробки (LxVxH)	400x260x250mm	
Box Weight - Poids de la boîte - Peso caja de carton - Peso caixa de cartão - Peso scatola - Kartonschachtel Gewicht - Вес коробки	6,3 Kg	
PCS per Masterbox - PCS par Masterbox - PCS por Masterbox - PCS por Masterbox Pezzi per masterbox - Stücke für die Masterbox - количество для мастер-бокса	1 PCS	
PCS per Euro Pallet - PCS par Euro Pallet - PCS por Euro Pallet - PCS por Euro Pallet Pezzi per Europallet - Stücke für die Europalette - Пьесы для европоддонов	63 PCS	
Code - Code - Código - Code - Codice - Code - код	52973	
Bar Code - Code barre - Código barra - Code à barres Codice a barre - Bestellcode - EAN	8004386529737	

EVO 200

STANLEY
FATMAX

ELECTRODES

Rutile - AWS E6013
Stainless Steels - AWS E308
Basic - AWS E7018



13,0 KVA

TECHNICAL SPECIFICATIONS	EVO 200	
Main Voltage - Tension de réseau - Voltaje de red - Tensão de rede Tensione di rete - Netzwerkspeisung - Сетевое напряжение	230V, 50-60Hz	
Absorbed Power - Puissance absorbée - Potencia absorbida - Potência absorvida - Potenza assorbita - Absorbierte Kraft - поглощенная мощность (MAX)	8,7 kVA 6,8 kW	MMA
No load Voltage - Tension à vide - Tensión en vacío - Tensão de vácuo - Tensione a vuoto - Vakuumspannung - Вакуумное напряжение	71V	
Welding Current - Courant de soudage - Corriente de soldadura - Corrente de soldagem - Corrente di saldatura - Schweißstrom - Сварочный ток	15-200A	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho - Fattore di servizio - Einschaltdauer - Соотношение прерывистости - EN 60974-1	20/200A	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho - Fattore di servizio - Einschaltdauer - Соотношение прерывистости - 20° C	200A@60%	
Min-Max Electrode - Electrode Min-Max - Electrodo min-max - Electrodo min-max - Elettrodo Min-Max - Elektrode min-max - Электрод min-max	1,6-5,0 mm	
Absorbed Power - Puissance absorbée - Potencia absorbida - Potência absorvida - Potenza assorbita - Absorbierte Kraft - поглощенная мощность (MAX)	5,9 kVA 4,5 kW	TIG LIFT
No load Voltage - Tension à vide - Tensión en vacío - Tensão de vácuo - Tensione a vuoto - Vakuumspannung - Вакуумное напряжение	14V	
Welding Current - Courant de soudage - Corriente de soldadura - Corrente de soldagem - Corrente di saldatura - Schweißstrom - Сварочный ток	15-200A	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho - Fattore di servizio - Einschaltdauer - Соотношение прерывистости - EN 60974-1	20/200A	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho - Fattore di servizio - Einschaltdauer - Соотношение прерывистости - 20° C	200A@60%	
Min-Max Electrode - Electrode Min-Max - Electrodo min-max - Electrodo min-max - Elettrodo Min-Max - Elektrode min-max - Электрод min-max	1,6-2,4 mm (tungsten)	
Box volume - Volume de la boîte - Volumen caja de carton - Volume caixa de cartão - Volume scatola - Kartonschachtel Volumen - Объем коробки	0,026m³	
Box Size - Taille de la boîte - Dimensiones caja de carton - Dimensões caixa de cartão - Dimensione scatola - Kartonschachtelgröße - Размер коробки (LxVxH)	400x260x250mm	
Box Weight - Poids de la boîte - Peso caja de carton - Peso caixa de cartão - Peso scatola - Kartonschachtel Gewicht - Вес коробки	6,6 Kg	
PCS per Masterbox - PCS par Masterbox - PCS por Masterbox - PCS por Masterbox Pezzi per masterbox - Stücke für die Masterbox - количество для мастер-бокса	1 PCS	
PCS per Euro Pallet - PCS par Euro Pallet - PCS por Euro Pallet - PCS por Euro Pallet Pezzi per Europallet - Stücke für die Europalette - Пьесы для европоддонов	63 PCS	
Code - Code - Código - Code - Codice - Code - код	52993	
Bar Code - Code barre - Código barra - Code à barres Codice a barre - Bestellcode - EAN	8004386529935	